

Teknik Parametreler

1300T-4500T



			HDC1300	HDC1650	HDC2000	HDC2500	HDC3000	HDC3500	HDC4000	HDC4500
Kitleme Gücü	Clamping force	kN	13000	16500	20000	25000	30000	35000	40000	45000
Kitleme Mesafesi	Clamping stroke	mm	1000	1200	1400	1500	1550	1600	1800	1900
İtici Kuvveti	Ejection force	kN	560	570	650	750	900	900	1000	1000
İtici Uzunluğu	Ejection stroke	mm	210	250	300	300	300	300	350	400
Kalıp Kalınlığı	Mold thickness (min-max)	mm	450-1200	500-1400	600-1600	750-1800	800-2000	800-2000	900-2100	900-2200
Plaka Boyutları	Platen Size (Horizontal x Vertical)	mm	1760x1760	2000x2000	2350x2250	2500x2500	2650x2650	2800x2700	2960x2900	3100x3000
Kolonlar Arası Mesafe	Tie Bar Spacing (Horizontal x Vertical)	mm	1100x1100	1250x1250	1450x1350	1600x1500	1650x1650	1750x1650	1850x1850	1965x1865
Kolon Çapı	Tie Bar Diameter	mm	Ø 230	Ø 260	Ø 290	Ø 320	Ø 340	Ø 350	Ø 390	Ø 410
Enjeksiyon Gücü	Injection Force (Intensified)	kN	1170	1295	1700	1700	2110	2410	2500	2500
Enjeksiyon Mesafesi	Injection stroke	mm	910	970	1050	1100	1250	1400	1600	1600
Piston Ucu Çapı	Plunger Tip Diameter	mm	100-140	110-150	130-170	140-180	150-190	160-200	160-200	180-220
Enjeksiyon Boyutu (Alüminyum)	Injection volume (aluminum)	kg	13.4-26.3	17.3-32.1	26.1-44.7	31.7-52.5	41.4-66.4	52.8-82.5	60.3-94.2	76.3-114
Döküm Basıncı	Casting Pressure (Intensified)	MPa	143-73	136-73	128-75	110-67	119-74	120-77	124-80	98-66
Döküm Alanı	Casting area	cm ²	910-1780	1210-2260	1562-2670	2270-3730	2510-4030	2915-4545	3217-5027	4580-6842
Max. Döküm Alanı	Maximum casting area (40MP)	cm ²	3250	4125	5000	6250	7500	8750	10000	11250
Enjeksiyon Pozisyonu	Injection position	mm	-160,-320	-175,-350	-175,-350	-200,-400	-250,-450	-300,-600	-300,-600	-300,-600
Piston Ucu Çıkıntısı	Plunger Tip Protrusion	mm	355	400	440	450	550	600	745	700
Ocak Çapı	Shot Sleeve Flange Diameter	mm	240	260	260	280	280	320	320	340
Piston Atış Alanı ile Sabit Plaka Arası Mesafe	Shot Sleeve Flange Protrusion From Fixed Platen	mm	25	25	30	30	30	35	35	35
Sistem Basıncı	System working pressure	MPa	21	21	21	21	21	21	21	21
Motor / Servo Motor Gücü	Motor power/servo motor power	kW	53.5x2	53.5x2	53.5x3	53.5x3	53.5x3	53.5x4	53.5x4	53.5x4
Yağ Tankı Kapasitesi	Hydraulic Oil Filling Volume	L	2100	2100	3300	3300	3400	3600	3700	3700
Makine Tonajı	Lifting reference weight	T	80	105	130	160	180	210	280	300
Makine Boyutu (Uzun. x Gen. x Yüks.)	Overall dimension (L x W x H)	mm	12100x4400x4200	13000x4500x4200	14500x4800x4400	14900x5400x4400	15600x5500x4500	16500x5800x4500	17800x5800x4800	18200x6000x5200